



TITAN

Waterproof TriCore

PRODUCT SPECIFICATIONS

Size	7" x 48"
Thickness	4.4 mm
Wear Layer	12 mil
Finish	DiamondGuard™ / HealthGuard™
Attached Pad	QuietStep Cushion™
Micro Beveled	Yes
Edge Traffic Use	Light Commercial
Installation	Floating Click / Unilin
Pieces Per Carton	16
SF Per Carton	38.45
Cartons Per Pallet	60
SF Per Pallet	2,307
Material	Waterproof TriCore™ / 100% Virgin

WARRANTY

12 Year Light Commercial / Limited Lifetime Residential

PERFORMANCE

ASTM F2055 Size	Pass
ASTM F386 Thickness	Pass
ASTM F2055 Squareness	Pass
ASTM F1914 Residual Indentation	Pass
ASTM F137 Flexibility	Pass
ASTM F2199 Dimensional Stability	Pass
ASTM F925 Chemical Resistance	Pass
ASTM F1514 Resistance to Heat	Pass
ASTM F1515 Resistance to Light	Pass
ASTM F 970 Static Load Limit	Pass
Certified Low Emitting Product	Meets Guidelines
Indoor Air Quality	Meets Guidelines
Indoor Sound Transmission Test	68 (s con i ion 6 concr sla wi ro c ilin)

