STYLED IN ITALY. PROUDLY AMERICAN.

RIDGE

MANANANANAN

atlas concorde USA

Traditional and rustic at first glance, this particular mix of stones features a raw look, which can quickly become young and informal. A touch of natural simplicity for giving comfort and personality to your spaces.

3-



COLORED BODY PORCELAIN STONEWARE

RIDGE



Greige

Anthracite

0

Ridge Ivory 11^{3/4}"x23^{5/8}" - 30x60 cm Ridge Beige Row Mosaic 11^{3/4}"x11^{3/4}" - 30x30 cm Ridge Ivory Bullnose 3"x24" - 7.2x60 cm

0 0

0

COLORED BODY PORCELAIN STONEWARE



Ivory







Greige



Anthracite

COLORED BODY PORCELAIN STONEWARE



RIDGE

Ridge Beige 11^{3/4}"x23^{5/8}" - 30x60 cm Ridge Beige Cove Base 6"x12" - 15x30 cm

REDEEM

Redeem Ash 7^{6/8}"x39^{3/8}" - 20x100 cm



FLOOR



Compliant with standards ANSI A137.1-2012



RIDGE

Ridge Greige 11^{3/4}"x23^{5/8}" - 30x60 cm Ridge Greige Bullnose 3"x24" - 7.2x60 cm



SIZE - THICKNESS

 $11^{3/4}$ "x $23^{5/8}$ " - 30x60 cm \neq 9 mm



RIDGE Ivory 11^{3/4}"x23^{5/8}" - 30x60 cm



RIDGE Beige 11^{3/4}"x23^{5/8}" - 30x60 cm



RIDGE Greige 11^{3/4}"x23^{5/8}" - 30x60 cm



RIDGE Anthracite 11^{3/4}"x23^{5/8}" - 30x60 cm

MOSAICS



RIDGE Ivory Mosaic 11^{3/4}"x11^{3/4}" - 30x30 cm (Mosaic 2"x2")



RIDGE Ivory Row Mosaic 11^{3/4}"x11^{3/4}" - 30x30 cm (Row Mosaic 2"x4")



RIDGE Beige Mosaic 11^{3/4}"x11^{3/4}" - 30x30 cm (Mosaic 2"x2")



RIDGE Beige Row Mosaic 11^{3/4}"x11^{3/4}" - 30x30 cm (Row Mosaic 2"x4")



RIDGE Greige Mosaic 11^{3/4}"x11^{3/4}" - 30x30 cm (Mosaic 2"x2")



RIDGE Greige Row Mosaic 11^{3/4}"x11^{3/4}" - 30x30 cm (Row Mosaic 2"x4")



RIDGE Anthracite Mosaic 11^{3/4}" x11^{3/4}" - 30x30 cm (Mosaic 2"x2")



RIDGE Anthracite Row Mosaic 11^{3/4}"x11^{3/4}" - 30x30 cm (Row Mosaic 2"x4")





Compliant with standards ANSI A137.1-2012



FLOOR



RIDGE

Ridge Beige Row Mosaic 11^{3/4}" x11^{3/4}" - 30x30 cm

RIDGE Ivory RIDGE Beige RIDGE Greige Bulnose 3"x 24" - 7.2x60 cm Cove base 6"x12" - 15x30 cm

COORDINATING TRIMS

KIIX.

🔷 atlas concorde U S A

Finish

Matte

11^{3/4}"x 23^{5/8}" - 30x60 cm 👗 9 mm

COLORED BODY PORCELAIN STONEWARE

P RCELAIN I FREE Member of FREE

FINISH

MATTE



Compliant with standards ANSI A137.1-2012

SIZE - THICKNESS



FIELD TILES - Available in all colors				
	Nominal size (in)	Thickness (mm)		
	11 3/4" x 23 5/8"	9 mm		

MODERATE	VARIATION

While the colors and/or texture present on a single piece of tile will be indicative of the colors and/or texture to be expected on the other tiles, the amount of colors and/or texture on each piece may vary significantly. It is recommended that the range be viewed before selection.

MOSAICS AND	COORDINATING	TRIMS -	Available in all colors
INICOAICO AND	COORDINATING	I NIIVIS -	Available in all colors

	Nominal size (in)	Thickness (mm)	Finish
Mosaic 2"x2"	11 3/4" x 11 3/4"	9 mm	Matte
Row Mosaic 2"x4"	11 3/4" x 11 3/4"	9 mm	Matte
Bullnose 3"x24"	2 7/8" x 23 5/8"	9 mm	Matte
Cove Base 6"x12"	5 7/8" x 11 3/4"	8.5 mm (*)	Matte

Please refer to caliber chart for work sizes.

Close joints are not recommended. (*): Cove Base thickness is 7 mm on flat top part.

PERFORMANCE & FEATURES

				Porcelain Tile Specification				
		PROPERTY	ASTM TEST METHOD	Calibrated		Rectified		
		PROPERTY		Minimum	Maximum	Minimum	Maximum	RIDGE
		Nominal Size	ASTM C499	-3.00%	3.00%	-3.00%	2.00%	Compliant
		Caliber Range (Variation from average facial dimension of sample)		-0.50% or -0.08 in (-2.0 mm) (*)	0.50% or 0.08 in (2.0 mm) (")	-0.25% or -0.03 in (-0.8 mm) (*)	0.25% or 0.03 in (0.8 mm) (*)	Compliant
REGULARITY	\searrow	Thickness ⁽¹⁾		N/A	Range: 0.40 in (1.02 mm)	N/A	Range: 0.40 in (1.02 mm)	Compliant
CHARACTERISTICS		Wedging	ASTM C502	-0.50% or -0.08 in (-2.0 mm) (*)	0.50% or 0.08 in (2.0 mm) (")	-0.25% or -0.03 in (-0.8 mm) (*)	0.25% or 0.03 in (0.8 mm) (*)	Compliant
	1 1 1	Warpage Edge		-0.75% or -0.09 in (-2.3 mm) (*)	0.75% or 0.09 in (2.3 mm) (*)	-0.40% or -0.05 in (-1.3 mm) ^[2] or -1.8 mm ^[3] (*)	0.40% or 0.05 in (1.3 mm) ^[2] or 1.8 mm ^[3] (*)	Compliant
	Warpage Diagonal	ASTM C485	-0.50% or -0.08 in (-2.0 mm) (*)	0.50% or 0.08 in (2.0 mm) (")	-0.40% or -0.07 in (-1.8 mm) (*)	0.40% or 0.07 in (1.8 mm) (*)	Compliant	
				All Porce	lain Tiles			
STRUCTURAL CHARACTERISTICS		Water Absorption	ASTM C373	≤ 0.5%			≤ 0.5%	
BULK MECHANICAL CHARACTERISTICS	$\frac{\downarrow}{\uparrow\uparrow}$	Breaking Strength	ASTM C648	Average ≥ 250 lbf. (1.11 kN) Individual ≥ 225 lbf. (1.00 kN)			≥ 350 lbf. avg	
PHYSICAL PROPERTIES		Bond Strength	ASTM C482	≥ 50 psi (0.34 Mpa)			≥ 100 psi	
THERMAL AND IGROMETRIC CHARACTERISTICS	ALK A	Resistance to Freeze/ Thaw Cycling	ASTM C1026	As Reported			Resistant	
CHEMICAL Chemical Resist		Chemical Resistance	ASTM C650	As Reported			Unaffected	
CHARACTERISTICS	Stain Resistance	ASTM C1378	As Reported			Unaffected		
SAFETY CHARACTERISTICS		Dynamic coefficient of friction	DCOF	Requires a minimum value of 0.42 for commercial areas that are likely to be wet			> 0.42 Wet	

(*) Whichever is less
(1) May not apply to textured surfaces or tiles with uneven back patterns.
(2) Whichever is less, for tiles up to 24*x24" (610 mm x 610 mm).
(3) Applies to tiles larger than 24"x24" (610 mm x 610 mm).

Atlas Concorde reserves the right to modify any product without notice and will not be liable for any direct or indirect damage resulting from such modifications. Colors and optical features of the materials illustrated in this catalogue are to be regarded as mere indications. For information and details relating to codes, packaging and weight it is recommended to refer to the latest pricelist.

 $\ensuremath{\textcircled{O}}$ Copyright Atlas Concorde USA, Inc. 2016 The reproduction of the work, fully or in part, is strictly forbidden.

Atlas Concorde Usa, Inc. 117 Seaboard Lane - Suite 170 Franklin, TN 37067 - USA

www.atlasconcordeusa.com